



14805 49th Street North • Clearwater, FL 33762
1-800-528-0997 U.S.A. only • (727) 523-8053 International

S-76C PRIMER

MATERIAL SAFETY DATA SHEET

PRODUCT: SEA HAWK S-76C HIGH BUILD EPOXY CATALYST

EMERGENCY TELEPHONE NUMBERS:

CHEMTREC: 800 424 9300
727 523 8053

UPDATE: 11/06/2003

BY: Clyde Garver

SECTION ONE: PRODUCT DESCRIPTION

NAME: Stronium Chromate Epoxy Primer Catalyst
CHEMICAL DESCRIPTION: Polyamide Solution
FORMULA: S-76C

SECTION TWO – HAZARDOUS INGREDIENTS

CHEMICAL	%	CAS NO.	TLV	PEL	SARA 302	SARA 313	CERCLA RQ#	CARCINOGEN Y/N			NOTE
								NTP	IARC	OSHA	
Xylene	58.8%	1330-20-7	100ppm	100ppm	N	Y	Y	N	N	N	(1)
Methal Isobutyl Ketone	11.5%	108-10-1	100ppm	50ppm	N	Y	N	N	N	N	(1)
Butanol	1.7%	71-36-3	50ppm	100ppm	N	Y	N	N	N	N	(1)

SECTION THREE: - PHYSICAL DATA

APPEARANCE: Liquid-Amer ODOR: Solvent
VAPOR PRESSURE: (mm of Hg.) : 9 mm of Hg
SPECIFIC GRAVITY (Water =1)
SOLUBILITY IN WATER: Slight

BOILING POINT: 237°F
VAPOR DENSITY: (Air=1): 3.66
VOTILE BY WEIGHT: 72%
EVAPORATION RATE: (Greater than 1):

SECTION FOUR – FIRE AND EXPLOSION DATA

FLASH POINT (° F / ° C) [CLOSED CUP] : 60° F

FLAMMABLE LIMIT: -LEL 1.1
-UEL 6.6

EXTINGUISHER MEDIA: Carbon Dioxide, Dry Chemical, Foam, and/or Water Fog

SPECIAL FIRE FIGHTING PROCEDURES: Fire fighter must wear self-contained breathing apparatus or air masks. Containers exposed to fire should be kept cool with water vapor.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION FIVE – HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section Two
EFFECTS OF OVEREXPOSURE

Inhalation: (ACUTE) Harmful if inhaled. May effect the brain, nervous or respiratory system, causing dizziness, headache, nausea or respiratory irritation. Overexposure can cause liver or kidney damage and CNS depression.
Skin Contact: Irritating upon repeated and prolonged contact.
Eye Contact: Corneal injury/eye damage

EMERGENCY & FIRST AID PROCEDURES:

Inhalation: Move subject to fresh air. If breathing is difficult, have trained person give oxygen if necessary, consult physician. If breathing has stopped, immediately give C.P.R, oxygen and obtain medical assistance
Eye/skin Contact: Flush eyes with large amounts of water for at least 15 minutes – see physician if irritation persists. Wash affected skin area with soap and water.

SECTION SIX – PHYSICAL HAZARDS (REACTIVITY DATA)

STABILITY: STABLE YES
UNSTABLE NO

CONDITIONS TO AVOID IF UNSTABLE: N/A
INCOMPATIBILITY WITH OTHER MATERIALS: Strong, oxidizers, acids, alkalies
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, carbon monoxide, smoke
HAZARDOUS POLYMERIZATION: Will not occur.
CONDITIONS TO AVOID UNCONTROLLED POLYMERIZATION: NA

SECTION SEVEN – STORAGE, HANDLING, SPILL AND DISPOSAL PROCEDURES

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store below 100° f /38° C, and in accordance with NFPA Code. Keep away from sparks or flame while stored, during use and until all vapors have dissipated. Extinguish pilot lights and all other sources of ignition. Keep area well ventilated. Use respirator if engineering controls are not adequate to maintain mist, vapor or dust below applicable standards.

STEPS TO FOLLOW IF MATERIAL IS SPILLED OR RELEASED: Remove all sources of ignition. Ventilate area. Use inert absorbent to collect residue, place in proper container, and dispose of proper container, and dispose of properly. Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Test for ignitability to determine applicable EPA hazardous waste numbers. See Section Two.

WASTE DISPOSAL METHODS: Incinerate in approved facility in accordance with all applicable regulations. Do not incinerate closed container. Avoid discharge into natural waters.

SECTION EIGHT – PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear Respirator (MSHA/NIOSH) suitable for concentration and types of contaminants.

VENTILATION: Local ☒ Other
Mechanical ☒

PROTECTIVE GLOVES: Impervious – Rubber, Neoprene.

EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1)

OTHER PROTECTIVE EQUIPMENT: NONE

SECTION NINE – SPECIAL PRECAUTIONS

None

OTHER PRECAUTIONS: Keep away from children, pets, livestock, and foodstuffs Not recommended for interior use.

SECTION TEN – OTHER REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65 CHEMICALS: This product contains substances which are known to the State of California to cause cancer and/or birth effects or reproductive harm.

TSCA CERTIFICATION: All Chemicals in this product are listed, or exempt from listing, on the TSCA Inventory.

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using the material in combination with any other material or any other process is the responsibility of the user. All materials present-unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third parties caused by this material. User assumes all risks associated with the use of this material

(1) Abbreviations: N/E – Not Established, Supp. Conf. – Supplier Confidential, N/A – Not Applicable, ppm – Parts Per Million, mg/m³ – Milligrams per cubic meter, N- NO, Y – YES.