



Product Name: **Hawk Catalyst C3**

Material Safety Data Sheet Page 1

New Nautical Coatings, Inc.
14805 49th Street North • Clearwater, FL 33762
1-800-528-0997 U.S.A. only • (727) 523-8053 International
www.SeaHawkPaints.com

CHEMTREC 24-HR EMERGENCY RESPONSE NUMBER
800-424-9300 • OUTSIDE US 703-527-3887
CHEMTREC should only be called in the event of chemical
emergencies involving spill, leak, fire, exposure, or accident
involving chemicals.

1. Product Identification

Product Name: **Hawk Catalyst C3**
Product Use: **Yacht Repair**
Appearance: **Liquid amber amine**
CAS Number: **Mixture**
Synonyms: **Modified aliphatic polyamine**

Revision Date: **March 2014**
Prepared by : **Chief Chemist**

2. Hazardous Ingredients

EMERGENCY OVERVIEW: DANGER! Corrosive to eyes and skin. Harmful if swallowed, inhaled or absorbed through the skin. Can cause allergic skin and respiratory reactions

EYE CONTACT: Moderate to severe irritation with possible tissue damage. Concentrated vapors can be absorbed in eye tissue and cause eye injury. Contact causes discomfort and possible corneal injury or conjunctivitis.

ACUTE SKIN CONTACT: May cause strong irritation, redness. Possible mild corrosion.

CHRONIC SKIN CONTACT: Prolonged or repeated contact may cause an allergic reaction and possible sensitization in susceptible individuals. Large dose skin contact may result in material being absorbed in harmful amounts.

ACUTE INHALATION: May cause respiratory tract irritation. Coughing and chest pain may result.

SYMPTOMS OF OVEREXPOSURE: Respiratory tract irritation. Skin irritation and redness. Possible allergic reaction seen as hives and rash. Eye irritation. Possible liver and kidney disorders upon long term skin absorption overexposures.

INGESTION: Single dose oral toxicity is moderate. May cause gastrointestinal tract irritation and pain. Aspiration hazard.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Chronic respiratory disease, asthma. Eye disease. Skin disorders and allergies.

CHRONIC INHALATION: May cause respiratory tract irritation, coughing, sore throat, shortness of breath or chest pain.

HMIS Rating: Health: 3 Flammability: 1 Reactivity: 0

**3. Composition/Information on Ingredients**

Hazardous Component	Cas Number	Percentage by Weight	Reg Agency	PPM	Notes	MG/M3	Notes
Reaction of TETA with phenol/ formaldehyde	32610-77-8	30-50	ACGIH TLV OSHA-PEL				
Polyethylenepoly-amine	68131-73-7	<25					
Teta	112-24-3	<10					
Tepa	112-57-2	<10					
Reaction of TETA and propylene oxide	26950-63-0	40-50	ACGIH-STEL				

4. First Aid Measures

EYE CONTACT: Hold one eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing the eye. Contact a poison control center for treatment advice.

SKIN CONTACT: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call poison control center or doctor for treatment advice. Wash contaminated clothing before reuse.

INHALATION: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth. Call a poison control center or doctor for further treatment advice.

INGESTION: Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

NOTE TO PHYSICIAN: There is no specific antidote for effects from overexposure to the material. Treatment should be directed at the control of symptoms and the clinical condition.

5. Fire Fighting Measures

FLASH POINT: >270 F

EXTINGUISHING MEDIA: Use dry chemical, carbon dioxide, water spray, or foam.

FIRE FIGHTING PROCEDURES: As in any fire, wear complete fire service protective equipment, including full-face MSHA/NIOSH approved or equivalent self-contained breathing apparatus. Use water to cool fire-exposed container/structure/protect personnel.

FIRE AND EXPLOSION HAZARDS: Can release vapors that form explosive mixtures. Vapors can travel to a source of ignition and flash back. Closed containers may explode when exposed to extreme heat (fire). Toxic vapors may be given off in a fire.

6. Spill and Leak Procedures

Stop spill/leak if no risk involved. Avoid breathing vapor. Eliminate All sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Ventilate area. Take up carefully to avoid hear and sparks. Use an inert absorbent to complete a clean-up. This material reacts with oxidizing materials. Dispose of contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.



7. Handling and Storage

HANDLING: Avoid breathing of vapors, mists or fumes. Do not get on the skin, in eyes or on clothing. Spray paint in accordance with OSHA 29 CFR 1910.107. Use with adequate ventilation. Wash thoroughly after handling.

STORAGE: Store in cool, dry place away from high temperatures and moisture. Keep container tightly closed.

STORAGE TEMPERATURE (min./max.): 40°F (4°C) / 90°F (32°C).

8. Exposure Controls/Personal Protection

ENGINEERING CONTROLS: Ventilation is normally required when handling or using this product to keep exposure to airborne contaminants below the exposure limit. Facilities storing or utilizing this product should be equipped with and eyewash station and shower.

RESPIRATORS: Ensure fresh air entry during the application and drying. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, or if air monitoring demonstrates vapor level is above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved or equivalent) during and after application. Respirator selection, use and maintenance should be in accordance with the requirements in 29 CFR 1910.134 and NIOSH 42 CFR 84, whenever workplace conditions warrant a respirator's use.

PERSONAL PROTECTIVE EQUIPMENT: Industrial safety glasses at a minimum. As necessary for work conditions: use side shields, goggles, or face shield. As required, chemical resistant flexible-type gloves (heavy duty neoprene or equal). Wear industrial type-work clothing and safety footwear. Depending on working conditions, i.e., contact potential, wear resistant protective garments such as head/neck cover, aprons, jackets, paints, coveralls, boots, etc.

9. Physical and Chemical Properties

Weight Per Gallon: 8.89LBS
Vapor Pressure: <1mmHg @ 68F/ 20C
pH: Alkaline
Solubility in Water: Appreciable
Color: light yellow

% Volatile by Weight: 0.07 lb/gal mixed
vapor density; heavier than air
Specific Gravity: 1.07
Viscosity: 90-100KU
Odor: ammonia-like

10. Stability and Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur.

Incompatibility: Avoid oxidizing agents, heat, sparks, and open flames.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, oxides of nitrogen and other toxic organic compounds.

11. Toxicological Information

Acute Oral Effects(LD50): (rat) 1000-2000 mg/kg (components)

Acute dermal Toxicity(LD 50): (rabbit) 1000-2000 mg/kg (components)

Sensitization: skin contact may cause an allergic skin reaction

Skin and eye Irritation: skin burns and corrosive to eyes

12. Ecological Information

Product has not been tested for ecological toxicity.

13. Disposal Considerations

Dispose of unusable product in accordance with local, state, and federal regulations.

14. Transportation Information

DOT Non- Bulk	IMDG	ICAO/IATA
Shipping name: Polyamine,	Shipping name: Polyamine	Shipping name: polyamine
Technical shipping name:propylenediamine	Technical shipping name:Propylenediamine	Technical shipping: Propylenediamine
Hazard Class: class 8	Hazard class: Class 8	Hazard class: Class 8
U.N/N.A Number: UN 2735	U.N. Number: UN2735	U.N. Number: UN2735
Packing Group: PG II	Packaging Group: PGII	Packaging Group: PGII
Marine Pollutant: No	marine Pollutant: no	Marine Pollutant: no

15. Regulatory Information

SARA TITLE III SECTION 313 CHEMICALS: contain phenol

OSHA STATUS: Corrosive ; sensitizer

TSCA STATUS :All components listed on TSCA inventory or otherwise comply with TSCA requirements

CEPA Chemical Inventory Status: All components are listed DSL

STATE REGULATORY INFORMATION: The following chemicals are regulated by states. For information contact your local agency in your state.

COMPONENT NAME(CAS#)

CONCENTRATION

STATE CODE

TEPA (112-57-2)

MA,NJ,PA

TETA (112-24-30)

MA,NJ,PA

Phenol (108-95-2)

NJ,RI,PA,MA,IL

Canada WHMIS Classification: Toxic material causing other toxic effects, corrosive material

EPA REGISTRATION: N/A

Globally Harmonized System



Corrosive



Irritant



Health Hazard

16. Other Information

NOTICE: This document is generated for the purpose of distributing health, safety, and environmental data. The information on this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. New Nautical Coatings, Inc. makes no warranty with respect thereto and disclaims all liability from reliance thereon.